



*NOTE: ALL relevant materials are complied with ROHS directive

1049			
P1		P2	
1	—————	8	BROWN
2	—————	3	RED
3	—————	2	ORANGE
4	—————	20	YELLOW
5	—————	7	GREEN
6	—————	6	BLUE
7	—————	4	PURPLE
8	—————	5	GREY
9	—————	22	BLACK
SHIELD	—————	SHIELD	

6	BLACK PVC TUBE ϕ 3.0*30mm
	ALUMINUM FOIL 33*110mm
	MOLDED PE COLOR TRANSPARENT
	MOLDED PVC BEIGE
5	BLACK PVC TUBE ϕ 3.0*22mm
	ALUMINUM FOIL 33*65mm
	MOLDED PVC BEIGE
4	NON-UL 9C 28AWG, ALUM-MYLAR FOIL SHIELDING WITH DRAIN WIRE, OD 5.0mm, JACKET BEIGE, DRAWING No. EMAL2809C-051
3	MOLDED THUMBSCREW #4-40, LENGTH 46.5mm, BEIGE
2	DB25 MALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR
1	DB9 FEMALE, GOLD FLASH ON CONTACTS, BLUE INSULATOR
No.	DESCRIPTION

APPROVED			Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm↑ ±40mm
CHECKED	HU		
DRAWING	ZHU		
DATE	05/JULY/19	ITEM NO.	SP-09F25MAT-XXX
			UNIT:mm